

Technische Daten

Für allgemeine Anwendungen (z. B. Agrartechnik & Bauindustrie),
Austauschbarkeit gemäß ISO 16028

Material:

Gehäuse: Stahl
Dichtung: Buna-N (Nitril)

Oberfläche:

Material: Chrom III PLUS
Beständigkeit gegen Weißrost [h]: 200
Beständigkeit gegen Rotrost [h]: 400
Temperaturbereich: -20°C bis +100°C

Technical data

For general applications (eg. agricultural technology and construction
industry), interchangeable according to ISO 16028

Material:

Housing: Steel
Seal: Buna-N (Nitril)

Surface:

Material: Cr III PLUS
Resistance against white rust [h]: 200
Resistance against red rust [h]: 400
Temperature range: -20°C to +100°C

| Anschlussart Connection type | PN (bar) WP (bar) | BG | DN DN | Size Size | Zoll Inch | G G | L ₃ (mm) L ₃ (mm) | Ø D (mm) Ø D (mm) | SW (mm) SW (mm) | Artikelnummer Article number |
|---------------------------------|---|----|----------|--------------|--------------|---------|--|----------------------|--------------------|---------------------------------|
| | BSP-Innengewinde DIN 3852 BSP female thread DIN 3852 | | | | | | | | | |
| | 350 | 1 | 6 | 04 | 1/4 | 1/4 | 58,2 | 28,0 | 20 | VC-FF-IG1/4-06M |
| | 300 | 2 | 10 | 06 | 3/8 | 3/8 | 68,2 | 32,0 | 24 | VC-FF-IG3/8-10M |
| | 300 | 2 | 10 | 06 | 3/8 | 1/2 | 72,2 | 32,0 | 27 | VC-FF-IG1/2-10M |
| | 300 | 3 | 12 | 08 | 1/2 | 1/2 | 75,0 | 38,0 | 32 | VC-FF-IG1/2-12M |
| | 250 | 3 | 12 | 08 | 1/2 | 3/4 | 79,0 | 38,0 | 36 | VC-FF-IG3/4-12M |
| | 250 | 4 | 16 | 10 | 5/8 | 3/4 | 80,0 | 42,0 | 36 | VC-FF-IG3/4-16M |
| 250 | 6 | 19 | 12 | 3/4 | 1 | 99,9 | 48,0 | 41 | VC-FF-IG1-20M | |
| | Metrisches Außengewinde ISO 8434-1-L Metric male-thread ISO 8434-1-L | | | | | | | | | |
| | 300 | 3 | 12 | 08 | 1/2 | M26x1,5 | 77,2 | 38,0 | 32 | VC-FF-CEL18-12M |


Zubehör

Staubschutz: Für Steckkupplung Serie VC-FF Muffe

| BG | DN DN | Size Size | Zoll Inch | Farbe Color | Material Material | Artikelnummer Article number |
|----|----------|--------------|--------------|----------------|----------------------|---------------------------------|
| | 1 | 6 | 04 | rot red | Kunststoff plastic | VC-FF-DP14-M |
| | 2 | 10 | 06 | rot red | Kunststoff plastic | VC-FF-DP38-M |
| | 3 | 12 | 08 | rot red | Kunststoff plastic | VC-FF-DP12-M |
| | 4 | 16 | 10 | rot red | Kunststoff plastic | VC-FF-DP34-M |
| | 6 | 20 | 12 | rot red | Kunststoff plastic | VC-FF-DP1-M |

Accessories

Dust protection: For plug-in coupling series VC-FF (sleeve)



Technische Daten

Für allgemeine Anwendungen (z. B. Agrartechnik & Bauindustrie),
Austauschbarkeit gemäß ISO 16028

Material:

Gehäuse: Stahl
Dichtung: Buna-N (Nitril)

Oberfläche:

Material: Chrom III PLUS
Beständigkeit gegen Weißrost [h]: 200
Beständigkeit gegen Rotrost [h]: 400
Temperaturbereich: -20°C bis +100°C

Technical data

For general applications (eg. agricultural technology and construction
industry), interchangeable according to ISO 16028

Material:

Housing: Steel
Seal: Buna-N (Nitril)

Surface:

Material: Cr III PLUS
Resistance against white rust [h]: 200
Resistance against red rust [h]: 400
Temperature range: -20°C to +100°C

| Anschlussart Connection type | PN (bar) WP (bar) | BG | DN DN | Size Size | Zoll Inch | G G | L ₂ (mm) L ₂ (mm) | Ø d (mm) Ø d (mm) | SW (mm) SW (mm) | Artikelnummer Article number |
|---------------------------------|---|----|----------|--------------|--------------|---------|--|----------------------|--------------------|---------------------------------|
| | BSP-Innengewinde DIN 3852 BSP female thread DIN 3852 | | | | | | | | | |
| | 350 | 1 | 6 | 04 | 1/4 | 1/4 | 49,2 | 16,1 | 20 | VC-FF-IG1/4-06S |
| | 300 | 2 | 10 | 06 | 3/8 | 3/8 | 55,8 | 19,7 | 24 | VC-FF-IG3/8-10S |
| | 300 | 2 | 10 | 06 | 3/8 | 1/2 | 59,8 | 19,7 | 27 | VC-FF-IG1/2-10S |
| | 300 | 3 | 12 | 08 | 1/2 | 1/2 | 72,0 | 24,5 | 32 | VC-FF-IG1/2-12S |
| | 250 | 3 | 12 | 08 | 1/2 | 3/4 | 76,0 | 24,5 | 36 | VC-FF-IG3/4-12S |
| | 250 | 4 | 16 | 10 | 5/8 | 3/4 | 75,5 | 27,0 | 36 | VC-FF-IG3/4-16S |
| | 250 | 6 | 20 | 12 | 3/4 | 1 | 93,8 | 30,0 | 41 | VC-FF-IG1-20S |
| | Metrisch Außengewinde ISO 8434-1-L Metric male-thread ISO 8434-1-L | | | | | | | | | |
| | 300 | 3 | 12 | 08 | 1/2 | M26x1,5 | 74,2 | 24,5 | 32 | VC-FF-CEL18-12S |

Zubehör

Staubschutz: Für Steckkupplung Serie VC-FF Stecker

| BG | DN DN | Size Size | Zoll Inch | Farbe Color | Material Material | Artikelnummer Article number |
|----|----------|--------------|--------------|----------------|----------------------|---------------------------------|
| | 1 | 6 | 04 | 1/4 | rot red | Kunststoff plastic VC-FF-DP14-S |
| | 2 | 10 | 06 | 3/8 | rot red | Kunststoff plastic VC-FF-DP38-S |
| | 3 | 12 | 08 | 1/2 | rot red | Kunststoff plastic VC-FF-DP12-S |
| | 4 | 16 | 10 | 5/8 | rot red | Kunststoff plastic VC-FF-DP34-S |
| | 6 | 20 | 12 | 3/4 | rot red | Kunststoff plastic VC-FF-DP1-S |

Accessories

Dust protection: For plug-in coupling series VC-FF (plug)